



www.auromageotex.com



AG Roofwrap Synthetic Underlayment

Auroma Geotex Synthetic Roofing Underlayment AG Roofwrap is a 4 layer synthetic underlayment. Its Top Side is made by sandwiching a layer of polypropylene woven scrim and a layer of polypropylene non-woven, and an anti-slip polyolefin coating on Bottom Side, engineered to extend the roof's lifeline. It is ideally used under fiberglass, asphalt and modified bitumen shingles, tile, slate and metal roofs.



Features & Benefits

- 1 Meets and Exceeds ASTM D4869, ASTM D226.
- 2 Easy Installation with printed lap lines and fastening points.
- 3 Lighter and Stronger than traditional Asphalt Felt-15#.
- 4 More material per roll than traditional Asphalt Felt-15#.
- 5 U.V. resistant up to 60 days exposure.
- 6 Non-Woven top and Anti-Slip coating offers a dynamic steep slope extraction.
- 7 100% water & air resistant.
- 8 No buckling, warping or cracking.
- 9 No mold growth, rot or dry out.
- 10 Available in 85 gm/m² to 180 gm/m² as per requirement.

Availability

Printing	up to 4 color High Quality Printing
Roll	48"x250' 10 square roll 19 lbs.
Packaging	64 rolls per pallet
Note	Customized sizes and colors available.
Note	Branding facility is also available.



Plot No. 236(236 & 238) Opp. Nirma Factory,
 Mehsana-Ahmedabad Highway, Baliyasan, Pin : 382732,
 Dist. Mehsana, Gujrat, (India) | CIN-U25209GJ2020PTC112481
 Phone: +91 93138 05646 / +91 93138 05648
 Email: info@auromageotex.com